

Scanner Scale

PDS



- Stainless-steel body
- Semipermanent structure
- Easy to read LED display
- Auto zero tracking

Model	PDS / PDS-P		PDI/SPS3326
Max. Capacity	15 kg	30 kg	15 kg
Readability	1/3,000 g		1/3,000 g
Display Digit	6 digits		
Display Type	LED (PDS) / LCD (PDS-P)		LED (PDS) / LCD (PDS-P)
Power	AC adapter 100 – 240V		AC adapter 100 – 240V
Operating Temperature	-10 – +40 °C		-10 – +40 °C
Platter Size (W) x (D)	299 x 299 mm		330 x 264 mm
Product Size (W) x (D) x (H)	348 x 348 x 121.2 mm		330 x 264 x 55.3 mm
Product Weight	10 kg		5.87 kg
Available Scanner	Metrologic (Honeywell) –MS7620 Horizon, MS 860 Datalogic - Megellan 2300 HS Motorola –symbol LS7808		-



Product Movie



ECR Interface Scale

PDN



- Tilt display, low profile
- Easy to read high brightness LED
- USB for power source and communication
- Connected to POS/ECR system

OPTION > Side display on body > Pole display

Model	PDN						
	Single interval			Dual interval			
Max. Capacity	6 kg	12 kg	30 kg	3/6 kg	6/15 kg	15/30 kg	15/32 kg
Readability	1 g	2 g	5g	1/2 g	2/5 g	5/10 g	5/10 g
Internal Resolution	1/60,000	1/60,000	1/60,000	1/60,000	1/60,000	1/60,000	1/60,000
External Resolution	1/6,000	1/6,000	1/6,000	1/3,000	1/3,000	1/3,000	1/3,000 1/3,200
Max. Tare	-5,999 kg	-11,998 kg	-29,995 kg	-2,999 kg	-5,998 kg	-14,995 kg	-14,995 kg
Display	94 x 28 mm / 3.7" x 1.1" 6 Digit LED						
Symbols	STABLE, ZERO, TARE, kg, lb, oz						
Keys	ZERO, TARE, FUNCTION						
Functions	Weighing, Unit conversion, ECR protocol, Printer protocol, BLE or USB Serial (Select only one)						
Platter Size (W) x (D)	380 x 280 mm						
Product Size (W) x (D) x (H)	384 x 308.4 x 81.8 mm						
Weight	5.6 kg						
Power	USB 5V or USB adapter (5V, 1000mA/Option)						
Operating Temperature	-10°C ~ +40°C / 14°F ~ 104°F						
Option	DEP-50, DLP-50 printer (RS-232C Only) / BLE module						

