



Q Search UISP products

[60 GHz Wireless](#)

[Wireless](#)

[Fiber](#)

[Wired](#)

[Accessory Tech](#)

Power Solutions > [sunMAX SolarPoint](#)



sunMAX SolarPoint

SM-SP-40

[Datasheet](#)

[Marketing Images](#)

[Installation Guide](#)

Mechanical

Dimensions	202 x 190 x 50 mm (8 x 7.5 x 2")
Weight	650 g (1.4 lb)
Enclosure material	UV-stabilized polycarbonate
Pole mount diameter	35 to 60 mm (1.4 to 2.4") on pipe outer diameter
Weatherproofing	IPX4

Hardware

Networking interface	(4) 10/100 MbE fast ports
Management interface	Ethernet WiFi
Power method	PV panel (H4 connectors)
Max. power consumption	2W
Supported voltage range	10–60V (Reverse protection, surge protection) Max. open circuit voltage: 60V

LEDs	System, output
Button	Factory reset
Ambient operating temperature*	-20 to 50° C (-4 to 122° F)
Certifications	FCC, IC, CE
NDAA Compliant	Yes

Software

Operating mode	AP
Security	WPA2-AES
Services	UISP, SNMP, NTP client, timezone, weather prediction service
Tools	Discovery, ping, traceroute over UISP app
Application requirements	UISP: Version 2.0.0 and later

[Compliance Information](#)

Stay in Touch

<input type="text" value="Email"/>	<input type="button" value="Subscribe"/>
------------------------------------	--



[Terms of Service](#) | [Privacy Policy](#) | [Legal](#) | [Cookies Settings](#)

© 2026 Ubiquiti, Inc. All rights reserved.