

Mobile Router Ultra

UMR-Ultra

£79.00

£94.80 VAT incl.



Ultra-compact managed LTE mobile router for IoT applications with integrated LTE, wired WAN, WiFi, automatic failover, and DC power input support.

The UMR series is a standalone mobile router, manageable via WiFi, Ethernet, or remotely with an optional Mobility Cloud subscription [mobility.ui.com](#), no UniFi Console required.

Setup and manage without a UniFi Console. [Lean More](#)

Power adapter and cable not included; please use a 10W USB-C or ATX power supply.

[Standard](#)

[Industrial](#)

[Ultra](#)

Powerful Accessories

UniFi Patch Cable

From **£1.50**
From **£1.80** VAT incl.

Universal Table Stand

£23.00
£27.60 VAT incl.

[Overview](#) **[Technical](#)** [In The Box](#) [Management](#)

Compare

[Installation Guide](#)

Overview

£79.00
£94.80 VAT incl.

1

[Add to Cart](#)

Networking Interface	(2) FE RJ45 ports, LTE Cat 4 radio, WiFi 4
SIM	Nano SIM
LTE Bands	B1, B2, B3, B4, B5, B7, B8, B12, B13, B18, B19, B20, B25, B26, B28, B66, B34, B38, B39, B40, B41
Mounting	DIN rail, Wall (Mounts Included)

Mechanical

Weight	Device: 200 g (7.1 oz) DIN rail/wall mounts: 20 g (0.7 oz)
Enclosure Material	Polycarbonate
Mount Material	Wall Mount: Polycarbonate DIN Rail Mount: Steel

Features

WAN

Priority & Fallback	✓
Cellular	✓
WiFi	✓
Ethernet	✓
LTE Passthrough mode	✓
Ethernet Bridge Mode	✓
VPN Client	
OpenVPN	✓
WireGuard	✓
Site-to-Site VPN	
IPsec	✓
WireGuard	✓
WiFi Standard	WiFi 4
Port Forwarding	✓
Firewall	✓
Static Routes	✓

Networking

Supported Data Rates

802.11n	6.5 Mbps to 150 Mbps (MCS0 - MCS7, HT 20/40)
802.11g	6, 9, 12, 18, 24, 36, 48, 54 Mbps
802.11b	1, 2, 5.5, 11 Mbps

Management	Ethernet WiFi
LTE Throughput Speed	Download 150 Mbps / Upload 50 Mbps
Antennas	
Ports	(1) Mobile 1: SMA female (1Rx) (1) Mobile 2: SMA female (1Tx/1Rx) (1) WiFi: RP-SMA female
Type	(2) External LTE antenna (1) External WiFi
Max. TX Power	17 dBm
WiFi MIMO	1 x 1
Max. Power Consumption	5.7W
Power Method	USB Type-C (5V DC/2A), 4-pin ATX DC (9—30V DC)
Buttons	(1) Factory reset
Ambient Operating Temperature	-30 to 70° C (-22 to 158° F)
Ambient Operating Humidity	10 to 90% noncondensing
Certifications	CE, UKCA, Anatel: 04867-25-08356

Stay in Touch



[Terms and Conditions](#) | [Terms of Service](#) | [Privacy Policy](#) | [Return Policy](#) | [Cookies Settings](#) | [FAQ](#)

© 2026 Ubiquiti, Inc. All rights reserved.